

# NFRC Product Line Summary (2020 Std)

Simulation Report # FLE23003-SS

**Manufacturer:** Fleetwood Windows & Doors

**Product Line ID:** FLE-M-106

**Simulation Orig Report Date:** 7/7/2023

**Series/Model:** Series 3200-T Swinging Door

**Model Size:** 960mm x 2090mm

**Simulation Revision Date:** 7/7/2023

**Operator Type:** Single Door-Stile & Rail

**Frame Abs.:** 0.3

**Report Type:** Recertification

**Frame Type:** Aluminum w/Thermal Breaks (AT)

**Simulation Lab Code:** SWWW

**Sash Type:** Aluminum w/Thermal Breaks (AT)

*Note: Options without numbers are grouped with the option(s) above*

Option	Description/Code	Glass Thicknesses	Gap Width(s)	Gas	Emissivity(sfc)	Spacer/Seal	Divider	U-Factor	CR	Tint	No Dividers		Dividers < 1"		Dividers > 1"	
											SHGC	VT	SHGC	VT	SHGC	VT
462	CIG366/Arg 5mm SS-D	0.197, 0.197	0.632	ARG	0.020(2)	SS-D	N,G	<b>0.44</b>	<b>41</b>	CL	<b>0.20</b>	0.42	<b>0.17</b>	0.36	<b>0.15</b>	0.31
463	CIG366/Arg 6mm SS-D	0.236, 0.236	0.522	ARG	0.020(2)	SS-D	N,G	<b>0.43</b>	<b>41</b>	CL	<b>0.20</b>	0.41	<b>0.17</b>	0.35	<b>0.16</b>	0.30
464	CIG366-i89/Arg 5mm SS-D	0.197, 0.197	0.632	ARG	0.020(2) 0.149(4)	SS-D	N,G	<b>0.40</b>	<b>41</b>	CL	<b>0.19</b>	0.41	<b>0.17</b>	0.35	<b>0.15</b>	0.30
465	CIG366-i89/Arg 6mm SS-D	0.236, 0.236	0.522	ARG	0.020(2) 0.149(4)	SS-D	N,G	<b>0.40</b>	<b>41</b>	CL	<b>0.19</b>	0.40	<b>0.17</b>	0.35	<b>0.15</b>	0.29
466	CIG272/Arg 5mm SS-D	0.197, 0.197	0.632	ARG	0.042(2)	SS-D	N,G	<b>0.44</b>	<b>41</b>	CL	<b>0.28</b>	0.46	<b>0.25</b>	0.40	<b>0.22</b>	0.34
467	CIG272/Arg 6mm SS-D	0.236, 0.236	0.522	ARG	0.042(2)	SS-D	N,G	<b>0.44</b>	<b>41</b>	CL	<b>0.28</b>	0.46	<b>0.25</b>	0.39	<b>0.22</b>	0.33
468	CIG272-i89/Arg 5mm SS-D	0.197, 0.197	0.632	ARG	0.042(2) 0.149(4)	SS-D	N,G	<b>0.40</b>	<b>41</b>	CL	<b>0.28</b>	0.45	<b>0.24</b>	0.39	<b>0.21</b>	0.33
469	CIG272-i89/Arg 6mm SS-D	0.236, 0.236	0.522	ARG	0.042(2) 0.149(4)	SS-D	N,G	<b>0.40</b>	<b>41</b>	CL	<b>0.27</b>	0.45	<b>0.24</b>	0.38	<b>0.21</b>	0.33
470	CIG180/Arg 5mm SS-D	0.197, 0.197	0.632	ARG	0.068(2)	SS-D	N,G	<b>0.45</b>	<b>41</b>	CL	<b>0.42</b>	0.51	<b>0.37</b>	0.44	<b>0.32</b>	0.37
471	CIG180/Arg 6mm SS-D	0.236, 0.236	0.522	ARG	0.068(2)	SS-D	N,G	<b>0.44</b>	<b>41</b>	CL	<b>0.41</b>	0.50	<b>0.36</b>	0.43	<b>0.31</b>	0.37
472	CIG180-i89/Arg 5mm SS-D	0.197, 0.197	0.632	ARG	0.068(2) 0.149(4)	SS-D	N,G	<b>0.41</b>	<b>41</b>	CL	<b>0.41</b>	0.50	<b>0.36</b>	0.43	<b>0.31</b>	0.36
473	CIG180-i89/Arg 6mm SS-D	0.236, 0.236	0.522	ARG	0.068(2) 0.149(4)	SS-D	N,G	<b>0.40</b>	<b>41</b>	CL	<b>0.40</b>	0.49	<b>0.35</b>	0.42	<b>0.30</b>	0.36
474	Clear/Air 5mm A1-D	0.197, 0.197	0.621	AIR		A1-D	N,G	<b>0.58</b>	<b>39</b>	CL	<b>0.49</b>	0.52	<b>0.43</b>	0.45	<b>0.37</b>	0.38
475	Clear/Air 6mm A1-D	0.236, 0.236	0.542	AIR		A1-D	N,G	<b>0.58</b>	<b>39</b>	CL	<b>0.48</b>	0.52	<b>0.42</b>	0.45	<b>0.36</b>	0.38
476	SN68/Air 5mm A1-D	0.197, 0.197	0.621	AIR	0.039(2)	A1-D	N,G	<b>0.48</b>	<b>40</b>	CL	<b>0.27</b>	0.44	<b>0.23</b>	0.38	<b>0.21</b>	0.33
	sBZ-SN68/Air 5mm A1-D	0.197, 0.197	0.621	AIR	0.039(3)	A1-D	N,G	<b>0.48</b>	<b>40</b>	BZ	<b>0.24</b>	0.29	<b>0.21</b>	0.25	<b>0.19</b>	0.21
477	SN68/Air 6mm A1-D	0.236, 0.236	0.542	AIR	0.039(2)	A1-D	N,G	<b>0.48</b>	<b>40</b>	CL	<b>0.26</b>	0.44	<b>0.23</b>	0.38	<b>0.20</b>	0.32
	sBZ-SN68/Air 6mm A1-D	0.236, 0.236	0.542	AIR	0.039(3)	A1-D	N,G	<b>0.48</b>	<b>40</b>	BZ	<b>0.23</b>	0.26	<b>0.20</b>	0.23	<b>0.18</b>	0.19
478	SN68/Arg 5mm A1-D	0.197, 0.197	0.621	ARG	0.039(2)	A1-D	N,G	<b>0.45</b>	<b>40</b>	CL	<b>0.26</b>	0.44	<b>0.23</b>	0.38	<b>0.20</b>	0.33
479	SN68/Arg 6mm A1-D	0.236, 0.236	0.542	ARG	0.039(2)	A1-D	N,G	<b>0.45</b>	<b>40</b>	CL	<b>0.26</b>	0.44	<b>0.23</b>	0.38	<b>0.20</b>	0.32
480	SNX62/Air 5mm A1-D	0.197, 0.197	0.621	AIR	0.020(2)	A1-D	N,G	<b>0.48</b>	<b>40</b>	CL	<b>0.19</b>	0.40	<b>0.17</b>	0.35	<b>0.15</b>	0.30
481	SNX62/Air 6mm A1-D	0.236, 0.236	0.542	AIR	0.020(2)	A1-D	N,G	<b>0.47</b>	<b>40</b>	CL	<b>0.19</b>	0.40	<b>0.17</b>	0.34	<b>0.15</b>	0.29
482	SNX62/Arg 5mm A1-D	0.197, 0.197	0.621	ARG	0.020(2)	A1-D	N,G	<b>0.45</b>	<b>40</b>	CL	<b>0.19</b>	0.40	<b>0.17</b>	0.35	<b>0.15</b>	0.30
483	SNX62/Arg 6mm A1-D	0.236, 0.236	0.542	ARG	0.020(2)	A1-D	N,G	<b>0.45</b>	<b>40</b>	CL	<b>0.19</b>	0.40	<b>0.17</b>	0.34	<b>0.15</b>	0.29

The Condensation Resistance results obtained from this procedure are for controlled laboratory conditions and do not include the effects of air movement through the specimen, solar radiation, and the thermal bridging that may occur due to the specific design and construction of the fenestration system opening. (NFRC 500)

# NFRC Product Line Summary (2020 Std)

Simulation Report # FLE23003-SS

**Manufacturer:** Fleetwood Windows & Doors

**Product Line ID:** FLE-M-106

**Simulation Orig Report Date:** 7/7/2023

**Series/Model:** Series 3200-T Swinging Door

**Model Size:** 960mm x 2090mm

**Simulation Revision Date:** 7/7/2023

**Operator Type:** Single Door-Stile & Rail

**Frame Abs.:** 0.3

**Report Type:** Recertification

**Frame Type:** Aluminum w/Thermal Breaks (AT)

**Simulation Lab Code:** SWWW

**Sash Type:** Aluminum w/Thermal Breaks (AT)

*Note: Options without numbers are grouped with the option(s) above*

Option	Description/Code	Glass Thicknesses	Gap Width(s)	Gas	Emissivity(sfc)	Spacer/Seal	Divider	U-Factor	CR	Tint	No Dividers		Dividers < 1"		Dividers > 1"	
											SHGC	VT	SHGC	VT	SHGC	VT
484	SN68/Arg 5mm ZF-S	0.197, 0.197	0.625	ARG	0.039(2)	ZF-S	N,G	<b>0.44</b>	<b>42</b>	CL	<b>0.26</b>	0.44	<b>0.23</b>	0.38	<b>0.20</b>	0.33
485	SN68/Arg 6mm ZF-S	0.236, 0.236	0.538	ARG	0.039(2)	ZF-S	N,G	<b>0.44</b>	<b>42</b>	CL	<b>0.26</b>	0.44	<b>0.23</b>	0.38	<b>0.20</b>	0.32
486	SN68-IS20/Arg 5mm ZF-S	0.197, 0.197	0.625	ARG	0.039(2) 0.198(4)	ZF-S	N,G	<b>0.40</b>	<b>41</b>	CL	<b>0.26</b>	0.43	<b>0.23</b>	0.37	<b>0.20</b>	0.32
487	SN68-IS20/Arg 6mm ZF-S	0.236, 0.236	0.538	ARG	0.039(2) 0.198(4)	ZF-S	N,G	<b>0.40</b>	<b>41</b>	CL	<b>0.26</b>	0.43	<b>0.23</b>	0.37	<b>0.20</b>	0.32
488	SNX62/Arg 5mm ZF-S	0.197, 0.197	0.625	ARG	0.020(2)	ZF-S	N,G	<b>0.43</b>	<b>42</b>	CL	<b>0.19</b>	0.40	<b>0.17</b>	0.35	<b>0.15</b>	0.30
489	SNX62/Arg 6mm ZF-S	0.236, 0.236	0.538	ARG	0.020(2)	ZF-S	N,G	<b>0.43</b>	<b>42</b>	CL	<b>0.19</b>	0.40	<b>0.17</b>	0.34	<b>0.15</b>	0.29
490	SNX62-IS20/Arg 5mm ZF-S	0.197, 0.197	0.625	ARG	0.020(2) 0.198(4)	ZF-S	N,G	<b>0.40</b>	<b>41</b>	CL	<b>0.18</b>	0.39	<b>0.16</b>	0.34	<b>0.15</b>	0.29
491	SNX62-IS20/Arg 6mm ZF-S	0.236, 0.236	0.538	ARG	0.020(2) 0.198(4)	ZF-S	N,G	<b>0.40</b>	<b>41</b>	CL	<b>0.18</b>	0.39	<b>0.16</b>	0.34	<b>0.15</b>	0.29
492	SN68/Arg 5mm TS-D	0.197, 0.197	0.621	ARG	0.039(2)	TS-D	N,G	<b>0.44</b>	<b>41</b>	CL	<b>0.26</b>	0.44	<b>0.23</b>	0.38	<b>0.20</b>	0.33
493	SN68/Arg 6mm TS-D	0.236, 0.236	0.524	ARG	0.039(2)	TS-D	N,G	<b>0.44</b>	<b>41</b>	CL	<b>0.26</b>	0.44	<b>0.23</b>	0.38	<b>0.20</b>	0.32
494	SN68-IS20/Arg 5mm TS-D	0.197, 0.197	0.621	ARG	0.039(2) 0.198(4)	TS-D	N,G	<b>0.41</b>	<b>41</b>	CL	<b>0.26</b>	0.43	<b>0.23</b>	0.37	<b>0.20</b>	0.32
495	SN68-IS20/Arg 6mm TS-D	0.236, 0.236	0.524	ARG	0.039(2) 0.198(4)	TS-D	N,G	<b>0.41</b>	<b>41</b>	CL	<b>0.26</b>	0.43	<b>0.23</b>	0.37	<b>0.20</b>	0.32
496	SNX62/Arg 5mm TS-D	0.197, 0.197	0.621	ARG	0.020(2)	TS-D	N,G	<b>0.44</b>	<b>41</b>	CL	<b>0.19</b>	0.40	<b>0.17</b>	0.35	<b>0.15</b>	0.30
497	SNX62/Arg 6mm TS-D	0.236, 0.236	0.524	ARG	0.020(2)	TS-D	N,G	<b>0.43</b>	<b>41</b>	CL	<b>0.19</b>	0.40	<b>0.17</b>	0.34	<b>0.15</b>	0.29
498	SNX62-IS20/Arg 5mm TS-D	0.197, 0.197	0.621	ARG	0.020(2) 0.198(4)	TS-D	N,G	<b>0.40</b>	<b>41</b>	CL	<b>0.18</b>	0.39	<b>0.16</b>	0.34	<b>0.15</b>	0.29
499	SNX62-IS20/Arg 6mm TS-D	0.236, 0.236	0.524	ARG	0.020(2) 0.198(4)	TS-D	N,G	<b>0.40</b>	<b>41</b>	CL	<b>0.18</b>	0.39	<b>0.17</b>	0.34	<b>0.15</b>	0.29
500	CIG272-Clr-CIG180/Arg 5mm SS-D	0.197, 0.197, 0.197	0.462, 0.462	ARG	0.042(2) 0.068(5)	SS-D	N,G	<b>0.36</b>	<b>42</b>	CL	<b>0.26</b>	0.40	<b>0.23</b>	0.35	<b>0.20</b>	0.30
501	CIG272-Clr-CIG180/Arg 6mm SS-D N	0.236, 0.236, 0.236	0.396, 0.396	ARG	0.042(2) 0.068(5)	SS-D	N	<b>0.37</b>	<b>43</b>	CL	<b>0.25</b>	0.39				
502	CIG272-Clr-CIG180/Arg 6mm SS-D Rect	0.236, 0.236, 0.236	0.396, 0.396	ARG	0.042(2) 0.068(5)	SS-D	G	<b>0.38</b>	<b>43</b>	CL			<b>0.22</b>	0.34		
503	CIG272-Clr-CIG180/Arg 6mm SS-D Cont	0.236, 0.236, 0.236	0.396, 0.396	ARG	0.042(2) 0.068(5)	SS-D	G	<b>0.38</b>	<b>43</b>	CL					<b>0.19</b>	0.29
504	CIG272-CIG180-i89/Arg 5mm SS-D	0.197, 0.197, 0.197	0.462, 0.462	ARG	0.042(2) 0.068(4) 0.149(6)	SS-D	N,G	<b>0.35</b>	<b>42</b>	CL	<b>0.24</b>	0.39	<b>0.22</b>	0.34	<b>0.19</b>	0.29
505	CIG272-CIG180-i89/Arg 6mm SS-D N	0.236, 0.236, 0.236	0.396, 0.396	ARG	0.042(2) 0.068(4) 0.149(6)	SS-D	N	<b>0.35</b>	<b>42</b>	CL	<b>0.24</b>	0.39				
506	CIG272-CIG180-i89/Arg 6mm SS-D Rect	0.236, 0.236, 0.236	0.396, 0.396	ARG	0.042(2) 0.068(4) 0.149(6)	SS-D	G	<b>0.36</b>	<b>42</b>	CL			<b>0.21</b>	0.33		
507	CIG272-CIG180-i89/Arg 6mm SS-D Cont	0.236, 0.236, 0.236	0.396, 0.396	ARG	0.042(2) 0.068(4) 0.149(6)	SS-D	G	<b>0.36</b>	<b>42</b>	CL					<b>0.19</b>	0.28

The Condensation Resistance results obtained from this procedure are for controlled laboratory conditions and do not include the effects of air movement through the specimen, solar radiation, and the thermal bridging that may occur due to the specific design and construction of the fenestration system opening. (NFRC 500)

# NFRC Product Line Summary (2020 Std)

Simulation Report # FLE23003-SS

**Manufacturer:** Fleetwood Windows & Doors

**Product Line ID:** FLE-M-106

**Simulation Orig Report Date:** 7/7/2023

**Series/Model:** Series 3200-T Swinging Door

**Model Size:** 960mm x 2090mm

**Simulation Revision Date:** 7/7/2023

**Operator Type:** Single Door-Stile & Rail

**Frame Abs.:** 0.3

**Report Type:** Recertification

**Frame Type:** Aluminum w/Thermal Breaks (AT)

**Simulation Lab Code:** SWWW

**Sash Type:** Aluminum w/Thermal Breaks (AT)

Note: Options without numbers are grouped with the option(s) above

Option	Description/Code	Glass Thicknesses	Gap Width(s)	Gas	Emissivity(sfc)	Spacer/Seal	Divider	U-Factor	CR	Tint	No Dividers		Dividers < 1"		Dividers > 1"	
											SHGC	VT	SHGC	VT	SHGC	VT
508	CIG180-Clr-CIG180/Arg 5mm SS-D	0.197, 0.197, 0.197	0.462, 0.462	ARG	0.068(2) 0.068(5)	SS-D	N,G	<b>0.36</b>	<b>42</b>	CL	<b>0.37</b>	0.44	<b>0.32</b>	0.38	<b>0.28</b>	0.33
509	CIG180-Clr-CIG180/Arg 6mm SS-D N	0.236, 0.236, 0.236	0.396, 0.396	ARG	0.068(2) 0.068(5)	SS-D	N	<b>0.37</b>	<b>43</b>	CL	<b>0.36</b>	0.43				
510	CIG180-Clr-CIG180/Arg 6mm SS-D Rect	0.236, 0.236, 0.236	0.396, 0.396	ARG	0.068(2) 0.068(5)	SS-D	G	<b>0.38</b>	<b>43</b>	CL			<b>0.31</b>	0.37		
511	CIG180-Clr-CIG180/Arg 6mm SS-D Cont	0.236, 0.236, 0.236	0.396, 0.396	ARG	0.068(2) 0.068(5)	SS-D	G	<b>0.38</b>	<b>43</b>	CL					<b>0.27</b>	0.32
512	CIG180-CIG180-i89/Arg 5mm SS-D	0.197, 0.197, 0.197	0.462, 0.462	ARG	0.068(2) 0.068(4) 0.149(6)	SS-D	N,G	<b>0.35</b>	<b>42</b>	CL	<b>0.35</b>	0.43	<b>0.31</b>	0.37	<b>0.27</b>	0.32
513	CIG180-CIG180-i89/Arg 6mm SS-D N	0.236, 0.236, 0.236	0.396, 0.396	ARG	0.068(2) 0.068(4) 0.149(6)	SS-D	N	<b>0.35</b>	<b>42</b>	CL	<b>0.34</b>	0.43				
514	CIG180-CIG180-i89/Arg 6mm SS-D Rect	0.236, 0.236, 0.236	0.396, 0.396	ARG	0.068(2) 0.068(4) 0.149(6)	SS-D	G	<b>0.36</b>	<b>42</b>	CL			<b>0.30</b>	0.37		
515	CIG180-CIG180-i89/Arg 6mm SS-D Cont	0.236, 0.236, 0.236	0.396, 0.396	ARG	0.068(2) 0.068(4) 0.149(6)	SS-D	G	<b>0.36</b>	<b>42</b>	CL					<b>0.26</b>	0.31
516	SN68-Clr-SN68/Air 5mm A1-D	0.197, 0.197, 0.197	0.468, 0.468	AIR	0.039(2) 0.039(5)	A1-D	N,G	<b>0.39</b>	<b>41</b>	CL	<b>0.23</b>	0.34	<b>0.20</b>	0.30	<b>0.18</b>	0.25
517	SN68-Clr-SN68/Air 6mm A1-D N	0.236, 0.236, 0.236	0.374, 0.374	AIR	0.039(2) 0.039(5)	A1-D	N	<b>0.41</b>	<b>41</b>	CL	<b>0.23</b>	0.34				
518	SN68-Clr-SN68/Air 6mm A1-D Rect	0.236, 0.236, 0.236	0.374, 0.374	AIR	0.039(2) 0.039(5)	A1-D	G	<b>0.42</b>	<b>41</b>	CL			<b>0.20</b>	0.29		
519	SN68-Clr-SN68/Air 6mm A1-D Cont	0.236, 0.236, 0.236	0.374, 0.374	AIR	0.039(2) 0.039(5)	A1-D	G	<b>0.42</b>	<b>41</b>	CL					<b>0.18</b>	0.25
520	SN68-Clr-SN68/Arg 5mm A1-D	0.197, 0.197, 0.197	0.468, 0.468	ARG	0.039(2) 0.039(5)	A1-D	N,G	<b>0.37</b>	<b>41</b>	CL	<b>0.23</b>	0.34	<b>0.20</b>	0.30	<b>0.18</b>	0.25
521	SN68-Clr-SN68/Arg 6mm A1-D N	0.236, 0.236, 0.236	0.374, 0.374	ARG	0.039(2) 0.039(5)	A1-D	N	<b>0.38</b>	<b>41</b>	CL	<b>0.23</b>	0.34				
522	SN68-Clr-SN68/Arg 6mm A1-D Rect	0.236, 0.236, 0.236	0.374, 0.374	ARG	0.039(2) 0.039(5)	A1-D	G	<b>0.39</b>	<b>41</b>	CL			<b>0.20</b>	0.29		
523	SN68-Clr-SN68/Arg 6mm A1-D Cont	0.236, 0.236, 0.236	0.374, 0.374	ARG	0.039(2) 0.039(5)	A1-D	G	<b>0.39</b>	<b>41</b>	CL					<b>0.18</b>	0.25
524	SNX62-Clr-SNX62/Air 5mm A1-D	0.197, 0.197, 0.197	0.468, 0.468	AIR	0.020(2) 0.020(5)	A1-D	N,G	<b>0.39</b>	<b>41</b>	CL	<b>0.17</b>	0.28	<b>0.15</b>	0.24	<b>0.13</b>	0.21
525	SNX62-Clr-SNX62/Air 6mm A1-D N	0.236, 0.236, 0.236	0.374, 0.374	AIR	0.020(2) 0.020(5)	A1-D	N	<b>0.41</b>	<b>41</b>	CL	<b>0.17</b>	0.28				
526	SNX62-Clr-SNX62/Air 6mm A1-D Rect	0.236, 0.236, 0.236	0.374, 0.374	AIR	0.020(2) 0.020(5)	A1-D	G	<b>0.42</b>	<b>41</b>	CL			<b>0.15</b>	0.24		
527	SNX62-Clr-SNX62/Air 6mm A1-D Cont	0.236, 0.236, 0.236	0.374, 0.374	AIR	0.020(2) 0.020(5)	A1-D	G	<b>0.42</b>	<b>41</b>	CL					<b>0.14</b>	0.20
528	SNX62-Clr-SNX62/Arg 5mm A1-D	0.197, 0.197, 0.197	0.468, 0.468	ARG	0.020(2) 0.020(5)	A1-D	N,G	<b>0.37</b>	<b>41</b>	CL	<b>0.17</b>	0.28	<b>0.15</b>	0.24	<b>0.13</b>	0.21
529	SNX62-Clr-SNX62/Arg 6mm A1-D N	0.236, 0.236, 0.236	0.374, 0.374	ARG	0.020(2) 0.020(5)	A1-D	N	<b>0.38</b>	<b>41</b>	CL	<b>0.17</b>	0.28				
530	SNX62-Clr-SNX62/Arg 6mm A1-D Rect	0.236, 0.236, 0.236	0.374, 0.374	ARG	0.020(2) 0.020(5)	A1-D	G	<b>0.39</b>	<b>41</b>	CL			<b>0.15</b>	0.24		
531	SNX62-Clr-SNX62/Arg 6mm A1-D Cont	0.236, 0.236, 0.236	0.374, 0.374	ARG	0.020(2) 0.020(5)	A1-D	G	<b>0.39</b>	<b>41</b>	CL					<b>0.13</b>	0.20

The Condensation Resistance results obtained from this procedure are for controlled laboratory conditions and do not include the effects of air movement through the specimen, solar radiation, and the thermal bridging that may occur due to the specific design and construction of the fenestration system opening. (NFRC 500)

# NFRC Product Line Summary (2020 Std)

Simulation Report # FLE23003-SS

**Manufacturer:** Fleetwood Windows & Doors

**Product Line ID:** FLE-M-106

**Simulation Orig Report Date:** 7/7/2023

**Series/Model:** Series 3200-T Swinging Door

**Model Size:** 960mm x 2090mm

**Simulation Revision Date:** 7/7/2023

**Operator Type:** Single Door-Stile & Rail

**Frame Abs.:** 0.3

**Report Type:** Recertification

**Frame Type:** Aluminum w/Thermal Breaks (AT)

**Simulation Lab Code:** SWWW

**Sash Type:** Aluminum w/Thermal Breaks (AT)

*Note: Options without numbers are grouped with the option(s) above*

Option	Description/Code	Glass Thicknesses	Gap Width(s)	Gas	Emissivity(sfc)	Spacer/Seal	Divider	U-Factor	CR	Tint	No Dividers		Dividers < 1"		Dividers > 1"	
											SHGC	VT	SHGC	VT	SHGC	VT
532	SN68-Clr-SN68/Arg 5mm ZF-S	0.197, 0.197, 0.197	0.438, 0.438	ARG	0.039(2) 0.039(5)	ZF-S	N,G	<b>0.36</b>	<b>43</b>	CL	<b>0.23</b>	0.34	<b>0.20</b>	0.30	<b>0.18</b>	0.25
533	SN68-Clr-SN68/Arg 6mm ZF-S N	0.236, 0.236, 0.236	0.375, 0.375	ARG	0.039(2) 0.039(5)	ZF-S	N	<b>0.37</b>	<b>43</b>	CL	<b>0.23</b>	0.34				
534	SN68-Clr-SN68/Arg 6mm ZF-S Rect	0.236, 0.236, 0.236	0.375, 0.375	ARG	0.039(2) 0.039(5)	ZF-S	G	<b>0.38</b>	<b>43</b>	CL			<b>0.20</b>	0.29		
535	SN68-Clr-SN68/Arg 6mm ZF-S Cont	0.236, 0.236, 0.236	0.375, 0.375	ARG	0.039(2) 0.039(5)	ZF-S	G	<b>0.38</b>	<b>43</b>	CL					<b>0.18</b>	0.25
536	SN68-SN68-IS20/Arg 5mm ZF-S	0.197, 0.197, 0.197	0.438, 0.438	ARG	0.039(2) 0.039(4) 0.198(6)	ZF-S	N,G	<b>0.35</b>	<b>42</b>	CL	<b>0.21</b>	0.33	<b>0.18</b>	0.29	<b>0.16</b>	0.24
537	SN68-SN68-IS20/Arg 6mm ZF-S N	0.236, 0.236, 0.236	0.375, 0.375	ARG	0.039(2) 0.039(4) 0.198(6)	ZF-S	N	<b>0.36</b>	<b>42</b>	CL	<b>0.20</b>	0.33				
538	SN68-SN68-IS20/Arg 6mm ZF-S Rect	0.236, 0.236, 0.236	0.375, 0.375	ARG	0.039(2) 0.039(4) 0.198(6)	ZF-S	G	<b>0.36</b>	<b>42</b>	CL			<b>0.18</b>	0.28		
539	SN68-SN68-IS20/Arg 6mm ZF-S Cont	0.236, 0.236, 0.236	0.375, 0.375	ARG	0.039(2) 0.039(4) 0.198(6)	ZF-S	G	<b>0.36</b>	<b>42</b>	CL					<b>0.16</b>	0.24
540	SNX62-Clr-SNX62/Arg 5mm ZF-S	0.197, 0.197, 0.197	0.438, 0.438	ARG	0.020(2) 0.020(5)	ZF-S	N,G	<b>0.36</b>	<b>43</b>	CL	<b>0.17</b>	0.28	<b>0.15</b>	0.24	<b>0.13</b>	0.21
541	SNX62-Clr-SNX62/Arg 6mm ZF-S N	0.236, 0.236, 0.236	0.375, 0.375	ARG	0.020(2) 0.020(5)	ZF-S	N	<b>0.37</b>	<b>43</b>	CL	<b>0.17</b>	0.28				
542	SNX62-Clr-SNX62/Arg 6mm ZF-S Rect	0.236, 0.236, 0.236	0.375, 0.375	ARG	0.020(2) 0.020(5)	ZF-S	G	<b>0.38</b>	<b>43</b>	CL			<b>0.15</b>	0.24		
543	SNX62-Clr-SNX62/Arg 6mm ZF-S Cont	0.236, 0.236, 0.236	0.375, 0.375	ARG	0.020(2) 0.020(5)	ZF-S	G	<b>0.38</b>	<b>43</b>	CL					<b>0.13</b>	0.20
544	SNX62-SNX62-IS20/Arg 5mm ZF-S	0.197, 0.197, 0.197	0.438, 0.438	ARG	0.020(2) 0.020(4) 0.198(6)	ZF-S	N,G	<b>0.34</b>	<b>42</b>	CL	<b>0.14</b>	0.27	<b>0.13</b>	0.24	<b>0.12</b>	0.20
545	SNX62-SNX62-IS20/Arg 6mm ZF-S N	0.236, 0.236, 0.236	0.375, 0.375	ARG	0.020(2) 0.020(4) 0.198(6)	ZF-S	N	<b>0.35</b>	<b>42</b>	CL	<b>0.15</b>	0.27				
546	SNX62-SNX62-IS20/Arg 6mm ZF-S Rect	0.236, 0.236, 0.236	0.375, 0.375	ARG	0.020(2) 0.020(4) 0.198(6)	ZF-S	G	<b>0.36</b>	<b>42</b>	CL			<b>0.13</b>	0.23		
547	SNX62-SNX62-IS20/Arg 6mm ZF-S Cont	0.236, 0.236, 0.236	0.375, 0.375	ARG	0.020(2) 0.020(4) 0.198(6)	ZF-S	G	<b>0.36</b>	<b>42</b>	CL					<b>0.12</b>	0.20
548	SN68-SN68-IS20/Arg 5mm TS-D	0.197, 0.197, 0.197	0.462, 0.462	ARG	0.039(2) 0.039(4) 0.198(6)	TS-D	N,G	<b>0.35</b>	<b>42</b>	CL	<b>0.21</b>	0.33	<b>0.18</b>	0.29	<b>0.16</b>	0.24
549	SN68-SN68-IS20/Arg 6mm TS-D N	0.236, 0.236, 0.236	0.399, 0.399	ARG	0.039(2) 0.039(4) 0.198(6)	TS-D	N	<b>0.35</b>	<b>41</b>	CL	<b>0.20</b>	0.33				
550	SN68-SN68-IS20/Arg 6mm TS-D Rect	0.236, 0.236, 0.236	0.399, 0.399	ARG	0.039(2) 0.039(4) 0.198(6)	TS-D	G	<b>0.36</b>	<b>41</b>	CL			<b>0.18</b>	0.28		
551	SN68-SN68-IS20/Arg 6mm TS-D Cont	0.236, 0.236, 0.236	0.399, 0.399	ARG	0.039(2) 0.039(4) 0.198(6)	TS-D	G	<b>0.36</b>	<b>41</b>	CL					<b>0.16</b>	0.24
552	SNX62-SNX62-IS20/Arg 5mm TS-D	0.197, 0.197, 0.197	0.462, 0.462	ARG	0.020(2) 0.020(4) 0.198(6)	TS-D	N,G	<b>0.35</b>	<b>42</b>	CL	<b>0.14</b>	0.27	<b>0.13</b>	0.24	<b>0.12</b>	0.20
553	SNX62-SNX62-IS20/Arg 6mm TS-D N	0.236, 0.236, 0.236	0.399, 0.399	ARG	0.020(2) 0.020(4) 0.198(6)	TS-D	N	<b>0.35</b>	<b>41</b>	CL	<b>0.14</b>	0.27				
554	SNX62-SNX62-IS20/Arg 6mm TS-D Rect	0.236, 0.236, 0.236	0.399, 0.399	ARG	0.020(2) 0.020(4) 0.198(6)	TS-D	G	<b>0.36</b>	<b>41</b>	CL			<b>0.13</b>	0.23		
555	SNX62-SNX62-IS20/Arg 6mm TS-D Cont	0.236, 0.236, 0.236	0.399, 0.399	ARG	0.020(2) 0.020(4) 0.198(6)	TS-D	G	<b>0.36</b>	<b>41</b>	CL					<b>0.12</b>	0.20

The Condensation Resistance results obtained from this procedure are for controlled laboratory conditions and do not include the effects of air movement through the specimen, solar radiation, and the thermal bridging that may occur due to the specific design and construction of the fenestration system opening. (NFRC 500)

