

NFRC Product Line Summary (2020 Std)

Simulation Report # FLE18001-2A-SS

Manufacturer: Fleetwood Windows & Doors

Product Line ID: FLE-M-109

Simulation Orig Report Date: 4/18/2018

Series/Model: Series 4070-T Exterior Glazed Sliding Door

Model Size: 2000mm x 2000mm

Simulation Revision Date: 6/7/2022

Operator Type: Sliding Glass Door-Sliding Glass Door (XX or OX)

Frame Abs.: 0.3

Report Type: Simple Addendum

Frame Type: Aluminum w/ Thermal Breaks - All Members (AT)

Simulation Lab Code: SWWW

Sash Type: Aluminum w/ Thermal Breaks - All Members (AT)

Note: Options without numbers are grouped with the option(s) above

Option	Description/Code	Glass Thicknesses	Gap Width(s)	Gas	Emissivity(sfc)	Spacer/Seal	Divider	U-Factor	CR	Tint	No Dividers		Dividers < 1"		Dividers > 1"	
											SHGC	VT	SHGC	VT	SHGC	VT
242	CIG366/Arg 8mm SS-D	0.315, 0.315	0.837	ARG	0.020(2)	SS-D	N,G	0.40	43	CL	0.22	0.48	0.20	0.42	0.17	0.36
243	CIG366-189/Arg 8mm SS-D	0.315, 0.315	0.837	ARG	0.020(2) 0.149(4)	SS-D	N,G	0.35	42	CL	0.21	0.46	0.19	0.41	0.17	0.35
244	CIG272/Arg 8mm SS-D	0.315, 0.315	0.837	ARG	0.042(2)	SS-D	N,G	0.40	43	CL	0.31	0.53	0.28	0.46	0.24	0.40
245	CIG272-189/Arg 8mm SS-D	0.315, 0.315	0.837	ARG	0.042(2) 0.149(4)	SS-D	N,G	0.36	42	CL	0.30	0.52	0.27	0.45	0.24	0.39
246	CIG180/Arg 8mm SS-D	0.315, 0.315	0.837	ARG	0.068(2)	SS-D	N,G	0.41	42	CL	0.46	0.58	0.40	0.51	0.36	0.44
247	CIG180-189/Arg 8mm SS-D	0.315, 0.315	0.837	ARG	0.068(2) 0.149(4)	SS-D	N,G	0.36	42	CL	0.44	0.57	0.39	0.50	0.34	0.43
248	Clear/Air 10mm A1-D	0.394, 0.394	0.749	AIR		A1-D	N,G	0.56	38	CL	0.55	0.61	0.48	0.53	0.42	0.46
249	SN68/Air 10mm A1-D	0.394, 0.394	0.749	AIR	0.039(2)	A1-D	N,G	0.45	39	CL	0.29	0.51	0.26	0.45	0.23	0.39
	sBZ-SN68/Air 10mm A1-D	0.394, 0.394	0.749	AIR	0.039(3)	A1-D	N,G	0.45	39	BZ	0.20	0.22	0.18	0.19	0.16	0.16
250	SN68/Arg 10mm A1-D	0.394, 0.394	0.749	ARG	0.039(2)	A1-D	N,G	0.42	39	CL	0.29	0.51	0.26	0.45	0.23	0.39
251	SNX62/Air 10mm A1-D	0.394, 0.394	0.749	AIR	0.020(2)	A1-D	N,G	0.44	39	CL	0.22	0.46	0.19	0.41	0.17	0.35
252	SNX62/Arg 10mm A1-D	0.394, 0.394	0.749	ARG	0.020(2)	A1-D	N,G	0.41	39	CL	0.21	0.46	0.19	0.41	0.17	0.35
253	SN68/Arg 10mm ZF-S	0.394, 0.394	0.750	ARG	0.039(2)	ZF-S	N,G	0.39	43	CL	0.29	0.51	0.26	0.45	0.23	0.39
254	SN68-IS20/Arg 10mm ZF-S	0.394, 0.394	0.750	ARG	0.039(2) 0.198(4)	ZF-S	N,G	0.35	42	CL	0.28	0.49	0.25	0.43	0.22	0.37
255	SNX62/Arg 10mm ZF-S	0.394, 0.394	0.750	ARG	0.020(2)	ZF-S	N,G	0.39	43	CL	0.21	0.46	0.19	0.41	0.17	0.35
256	SNX62-IS20/Arg 10mm ZF-S	0.394, 0.394	0.750	ARG	0.020(2) 0.198(4)	ZF-S	N,G	0.35	42	CL	0.20	0.45	0.18	0.39	0.16	0.34
257	SN68-IS20/Arg 10mm TS-D	0.394, 0.394	0.747	ARG	0.039(2) 0.198(4)	TS-D	N,G	0.36	41	CL	0.28	0.49	0.25	0.43	0.22	0.37
258	SNX62-IS20/Arg 10mm TS-D	0.394, 0.394	0.747	ARG	0.020(2) 0.198(4)	TS-D	N,G	0.35	42	CL	0.20	0.45	0.18	0.39	0.16	0.34

The Condensation Resistance results obtained from this procedure are for controlled laboratory conditions and do not include the effects of air movement through the specimen, solar radiation, and the thermal bridging that may occur due to the specific design and construction of the fenestration system opening. (NFRC 500, Sec. 4.4)



WESTLab

An NFRC Accredited
Simulation Laboratory

**ANSI/NFRC 100/200-2020/NFRC 500-2020
Simulation Report**

Manufacturer: Fleetwood Windows & Doors

Contact: Joe Zammit

**Address: 1 Fleetwood Way
Corona, CA 92879**

Phone: 951-279-1070

**ADDENDUM REPORT
Added Matrix Options
#242 - #258
(Add 8mm and 10mm
glass w/ all spacers)**

Model/Series: Series 4070-T Exterior Glazed Sliding Door

WESTLab Report No.:
FLE18001-2A-SS

WESTLab Report Date:
4/18/2018
Revision/Addendum Date:
6/7/2022

NFRC Product Line ID:
FLE-M-109
Report Type:
Simple Addendum

Operator Type: Sliding Glass Door-Sliding Glass Door (XX or OX)

Frame Type: Aluminum w/ Thermal Breaks - All Members (AT)

Sash Type: Aluminum w/ Thermal Breaks - All Members (AT)

Baseline Product for U-Factor Validation Testing:

Description: Simple Addendum - No validation unit required. See original WESTLab report FLE18001-HH for validation product details.

Simulated U-factor:

Test Size (mm): x

Physical Test Tolerance: to

Notes: *Manufacturer must have the product described above tested by an accredited physical testing laboratory. Physical test window U-factor results must be within the tolerance range listed above. The baseline product simulated U-factor is within 20% or 0.10 of the lowest simulated U-factor listed in the matrix (as allowed by ANSI/NFRC 100-2020) unless otherwise noted in the "Other Notes and Comments" section.*

**Signature of Simulator
In-Responsible-Charge:**

Staci Zastrow

Staci Zastrow, Certified Simulator

Disclaimers/Notes:

The window U-factor, SHGC, VT & CR values presented in this report were determined using the Therm and Window computer programs in full compliance with ANSI/NFRC 100-2020, ANSI/200-2020 and NFRC 500-2020, and from information supplied by the manufacturer. This report does not constitute certification of this product and only relates to the fenestration products simulated. Authorized use of any U-factor, SHGC Visible Transmittance and Condensation Resistance ratings may only be granted by the Certification Program Administrator. WESTLab does not imply or claim that the product simulated in this report will perform as stated in actual use conditions. This report is the property of WESTLab and the client, and must not be reproduced, except in full, without written approval from WESTLab and the client. Ratings values included in this report are for submittal to an NFRC-licensed IA are not meant to be used directly for labeling purposes. Only those values identified on a valid Certification Authorization Report (CAR) by an NFRC accredited Inspection Agency (IA) are to be used for labeling purposes. Rounding of values in this report is per NFRC 601 NFRC unit and measurement policy.

Ken Nittler: 1721 Arroyo Drive, Auburn, CA 95603. Phone: (530) 885-9891 e-mail: ken@westlab.net
Ross DePaola: 3473 Dell Drive, Madison, WI 53718-6629. Phone: (608) 221-9510, e-mail: ross@westlab.net
Jeff Baker: 4 Beck Blvd. Unit 7, Penetang, ON L9M 2H3. Phone: (613) 903-9798, e-mail: jeff@westlab.net