



Window Hardware

Hardware shown is standard finish brushed nickel. Some hardware is available in a black painted finish (requires less maintenance on the coast). For more detailed information, navigate to the appropriate product page and select the Hardware link in the Optional Features section online.

CASEMENT: SERIES 250-T & SERIES 2000



A



B



C



D



E



F



G




H




I

- A. Casement (Rotogear--Multi-Point Lock-Butt Hinges)
- B. Casement (Cam—4 Bar Stainless Hinges)
- C. Standard Folding Rotogear Operator¹ (Butt Hinges)
- D. Optional Knob Rotogear Operator¹ (Butt Hinges)
- E. Cam Handle² (4 Bar Stainless Hinges)
- F. Optional Ring Cam Handle (4 Bar Stainless Hinges)
- G. Custodial Lock (4 Bar Stainless Hinges)
- H. Standard Multipoint Lock
- I. Optional Cam w/Multipoint (Series 250-T only) (4 Bar Stainless Hinges)

AWNING: SERIES 250-T & SERIES 2000



A



B



C



D



E



F



G



H

- A. Awning Awning (Rotogear--Security Locks--4 Bar Stainless Hinges)
- B. Awning (Cam—4 Bar Stainless Hinges)
- C. Standard Folding Rotogear Operator³ (4 Bar Stainless Hinges)
- D. Optional Knob Rotogear Operator³ (4 Bar Stainless Hinges)
- E. Cam Handle (4 Bar Stainless Hinges)
- F. Optional Ring Cam Handle (4 Bar Stainless Hinges)
- G. Custodial Lock (4 Bar Stainless Hinges)
- H. Optional Security Lock⁴




¹Not intended to be left open when wind speeds exceed 10 mph.

²Approved to be left open during wind speeds of up to 25 mph.

³Limited vent travel. ⁴Recommended for security concerns.

HOPPER: SERIES 250-T & SERIES 2000



A



B



C



D



E



F

- A. Hopper
- B. Standard Ring Cam Handle* (4 Bar Stainless Hinges)
- C. Optional Spring Latch (4 Bar Stainless Hinges)
- D. Ring Pull* (4 Bar Stainless Hinges)
- E. Custodial Lock w/Wrench (4 Bar Stainless Hinges)
- F. Hopper Pole

All Hopper hardware available only with 4 Bar Hinges. *A single Ring Cam is provided on smaller windows. Wider vents receive two Ring Cam Handles and a Ring Pull in the middle.

CASEMENT, AWNING & HOPPER: HINGES



A



B



C



D

- A. 4 Bar Stainless Hinge (Series 250-T: C, A, H) (Series 2000: C, A, H)
- B. Aluminum Butt Hinge (4") (Series 250-T, 2000: C)
- C. Stainless Butt Hinge (3") (Series 250-T, 2000: C)
- D. Stainless Casement Limit Device (Series 250-T, 2000: C)

Availability of hinges is based on product series and operator type. For more detailed information, navigate to the appropriate product page and select the Hardware link in the Optional Features section online.

SCREENS



A



B



C



D




E


- A. Flat Screen—Stainless Clip (Series 250-T, 2000: C, A, H)
- B. Flat Screen—Stainless Clip (Close up)
- C. Hinged Screen—Stainless Hinge (Series 250-T, 2000: C, A)
- D. Hinged Screen—Stainless Hinge (Close up)
- E. Sliding Window Screen (Series 530-T, 510 & 250)

4 screen clips provided per screen. By default, awning hinged screen hinges are located across the top of the vent and casement screen hinges are located on the side of the vent.

SLIDING & SINGLE HUNG: LATCH & STRIKE



A



B



C



D

- A. Horizontal Slider
- B. Single Hung
- C. Stainless Latch & Strike (Series 530-T, 510 and 250)
- D. Angle View